


Letter Mailing Specifications

Folded Self-mailers, Stiched or Bound Mailers



Bar Code Clear Zone is where the postal bar code may be sprayed. **Do not place text in this zone**

 Minimum Size
 3.5" x 5"

 Maximum Size
 6" x 10.5"

Automation Aspect Ratio

Length divided by height must be between 1.3 and 2.5. If outside this aspect ratio, cannot mail at automation rates and subject to surcharges.

Minimum Thickness 9 pt Maximum Thickness 1/4" Maximum Weight 3 oz.

Minimum Paper Weight

Folded Self Mailers
Up to 1 oz. 70 lb.
1 oz. to 3 oz. 80 lb.

Stitched Booklet Covers

Up to 9" long 50 lb. Over 9"long 60 lb. **Address Block Clear Area**

Minimum $1^{1}/_{4}^{"} \times 3^{5}/_{16}^{"}$ Preferred $1^{1}/_{4}^{"} \times 4^{"}$

Address Block Position

Minimum from left or right 3/8"

Minimum from bottom 1/2"

Maximum from bottom
to top of block 4"

Address block must run horizontal

Address Panel Placement

Final fold at bottom Perpendicular folds at right Final folded panel opposite address (mail panel) side **Bar Code Specs**

or printing, except address lines 1/8'' Minimum distanct to address lines 1/25'' Minimum from bottom 5/8''

Maximum from bottom to top of bar code

Minimum distance to any type



 $3^{7}/8''$